

SW 50

Powered Subwoofer with Built-in Stereo Crossover



Congratulations on your new purchase and welcome to the AudioSource family of satisfied customers. We trust you will continue to enjoy the value and quality of your AudioSource SW 50 for many years to come. To ensure the best performance from your unit, please take a few moments to read this manual. Also, be sure to retain this document for future reference.

Note: If any part of this product is damaged or missing, do not contact your AudioSource dealer. Please call us directly at 800-435-7115.

Safety Instructions



Warning: To reduce the risk of fire or electric shock, do not expose this appliance to rain or moisture.

Caution: To reduce the risk of electric shock, do not remove cover (or back); no user serviceable parts inside.

Refer servicing to qualified service personnel.

Caution: To prevent electric shock, match wide blade of plug to wide slot, fully insert.

Attention: Pour éviter les chocs électriques, introduire la lame la plus large de la fiche dans la borne correspondante de la prise et pousser jusqu'au fond.

The lightning flash with arrowhead symbol, within an equilateral triangle, is intended to alert the user to the presence of uninsulated dangerous voltage within the product's enclosure that may be of sufficient magnitude to constitute a risk of electrical shock to persons.

The exclamation point within an equilateral triangle is intended to alert the user to the presence of important operating and maintenance (servicing) instructions in the literature accompanying the appliance.

Read Instructions

All the safety and operating instructions should be read before the appliance is operated.

Retain Instructions

The safety and operating instructions should be adhered to.

Heed Warnings

All warnings on the appliance and in the operating instructions should be adhered to.

Follow Instructions

All operating and use instructions should be followed.

Water and Moisture

The appliance should not be used near water. For example, near a bathtub, washbowl, kitchen sink, laundry tub, in a wet basement, or near a swimming pool, etc.

Ventilation

The appliance should be situated so that its location or position does not interfere with its proper ventilation. For example, the appliance should not be situated on a bed, sofa, rug, or similar surface that may block the ventilation openings; or, placed in a built-in situation, such as a bookcase or cabinet that may impede the flow of air through the ventilation openings.

Heat

The appliance should be situated away from heat sources such as radiators, heat registers, stoves, or other appliances (including amplifiers) that produce heat.

Power Sources

The appliance should be connected to a power supply only of the type described in the operating instructions or as marked on the appliance.

Grounding or Polarization

Precautions should be taken so that the grounding or polarization means of an appliance is not defeated.

Power Cord Protection

Power supply cords should be routed so that they are

not likely to be walked on or pinched by items placed on or against them, paying particular attention to cords at plugs, convenience receptacles, and the point where they exit from the appliance.

Cleaning

The appliance should be cleaned only as recommended by the manufacturer.

Power Lines

An outdoor antenna should be located away from power lines.

Non-Use Periods

The power cord of the appliance should be unplugged from the outlet when left unused for a long period of time.

Object and Liquid Entry

Care should be taken so that objects do not fall and liquids are not spilled into the enclosure through openings.

Damage Requiring Service

The appliance should be serviced by qualified service personnel when: a) The power supply cord or the plug has been damaged; b) Objects have fallen, or liquid has been spilled into the appliance; c) The appliance has been exposed to rain; d) The appliance does not appear to operate normally or exhibits a marked change in performance; or e) The appliance has been dropped, or the enclosure damaged.

Servicing

The user should not attempt to service the appliance beyond that described in the operating instructions. All other servicing should be referred to qualified service personnel.

Product Servicing

In the event your SW 50 fails to operate properly, please contact the dealer where you purchased the unit. Or you may contact AudioSource directly for further assistance.

SW 50

Powered Subwoofer with Built-in Stereo Crossover

SW 50 Overview

The AudioSource SW 50 represents the state of the art in powered subwoofers. The highly efficient ported enclosure houses a rugged eight-inch, reinforced driver, a fifty-watt amplifier, and a passive low frequency crossover network. This precision matched combination ensures the SW 50 will deliver the best sound possible, under even the most demanding conditions. The input level is variable over a wide range, allowing the SW 50 to complement a wide variety of systems. Line and hi level inputs are provided for fast and easy connection to virtually any system. The two-way auto power function completes the generous list of features offered by the SW 50.

A Few Words about Subwoofers

Subwoofers are designed to extend the bass response of your system beyond the limitations of most speakers. This unit is to be used in conjunction with, not in place of, your existing left and right speakers. The low frequency sounds reproduced by the subwoofer will radiate equally in all directions. It is not necessary to have a pair of subwoofers. A single subwoofer can dramatically enhance a stereo TV, a stereo system, or a full fledged home theater.

The advent of digital recording has increased the amount of low frequency information found on recorded material. Subwoofers are designed to accurately reproduce this bass. Similarly, most movies intended for home viewing feature bass well below the musical range of traditional loudspeakers. However, this information is vital to the impact, ambiance, and believability of a scene. A subwoofer enhances those elements in your home theater.

Placement Guidelines


Prior to installing your new AudioSource subwoofer, please consider the following guidelines. Placing the subwoofer near a wall or in a corner will greatly increase its bass response. As frequencies reproduced by subwoofers are long and need room to propagate, a subwoofer placed near the listening position will not sound as full as one placed farther away.

Finally, the cabinet of your AudioSource subwoofer is designed to blend in with most decors. If you decide to place anything directly atop your subwoofer, please use great caution, as the speaker cabinet will vibrate and items placed on top may shake loose or fall.

Using the Controls

Power

The *power* switch has two positions: *off* and *auto*. The *auto* position is the default setting. This keeps the amplifier in a standby mode. Using sophisticated signal sensing circuitry, the amplifier is instantaneously activated when a signal is detected at either of the inputs. If no signal is detected after several minutes, the amplifier switches back to the standby mode. The *off* position overrides this circuit, turning the subwoofer off manually. The *power* LED indicates the subwoofer's status.



Level

Since your subwoofer is designed to work in conjunction with other speakers, we have provided a *level* control will allow you to balance the output of your unit with the rest of your system. Once set, the level control should not require further adjustment. Begin with the level control at the minimum position. Slowly increase the level until the subwoofer's output is equal to that of your other speakers.

Note: Output level is relative and can be different from location to location. Always return to the normal listening location to evaluate any setting changes.

Connecting the SW 50

General Information

The diagrams on the following pages show three of the most common types of subwoofer connections. This information will guide you through the connection process.

First, a few words regarding the functioning of your powered subwoofer: All signals into your powered subwoofer will first pass through the crossover. The portion of the signal below the current crossover frequency setting will be reproduced by the subwoofer. The unprocessed signal will be passed to the hi level outputs. If you have a choice of connection options, remember that it may be easier to run long distances with speaker wire than with line connectors.

Hi Level In

These inputs are designed to accept an amplified signal from the speaker outputs of a receiver, power amp or other device not equipped with line level outputs.


Hi Level Out

The original amplified signal from your source is present at these outputs for connection to the existing left and right speakers.

Line In

These *RCA jacks* are designed to accept a line level signal from a receiver, pre-amp, surround sound decoder or similar device. When using a single line level output from another unit, a Y connector should be used to send the signal to both the left and right inputs. (Using the tape loop of a receiver or preamp is not recommended. Tape jacks typically send a constant level, regardless of the volume setting, unlike preamp outputs. This will affect the balance between the subwoofer and the rest of the system.)


Connecting the SW 50 (continued)



Hi Level Connections

Here the signal is already amplified as it leaves the receiver/amplifier. The speaker terminals of this unit are connected to the *hi level inputs* of the SW 50. The left and right speakers receive the original amplified signal from the SW 50 *hi level outputs*.

Connecting the SW 50 (continued)



Television Enhancement

Many newer television sets are equipped with *variable* stereo outputs. The signal available at these outputs varies with the television volume. In this situation, these variable audio outputs can be connected directly to the SW 50 *line inputs* to enhance the bass response of the television's built-in speakers.

Enjoy your new purchase. This manual provides detailed diagrams and instructions for setting up your equipment. Our commitment to your satisfaction doesn't end there. We also offer friendly assistance. Toll-free.

1-800-HELP-115

SW 50 Specifications

Amplifier Power Output	50 Watts
Frequency Response	40 Hz to 250 Hz
Signal to Noise Ratio	>90 dB
Driver	8" Reinforced
Functions	Power (Auto, Off) Input Level Control
Inputs	Hi Level (Speaker)In Line (RCA) In
Outputs	Hi Level (Speaker) Out
Dimensions	15" H x 11.5" W x 15" D
Weight	28 lbs.

Designs and specifications are subject to change without notice.

 **AudioSource®**

9300 North Decatur
Portland, Or 97203
Tel. 503.286.9300
Fax 503.978.3302
AUDIOSOURCE@PHOENIXGOLD.COM
www.audiosource.net

Printed in Canada